

Thanks to their versatility, our greenhouses are also used as shelters, covered storage structures for different necessities, e.g. for hay, farm equipment and other products, which require a covering.

They are designed to reach heights suitable for safely storing bulky farm equipment.


These storage structures are available in straight sided or tunnel design.



## TECHNICAL SPECIFICATIONS

- · Hot galvanized iron structure, highly resistant to corrosion
- Ø 60/76 and 3 mm thick side poles
- · Tie-beam and braces dimensioned according to the place installation and type of crop
- Arch spacing 2.00 to max 2.50 m
- The roof design varies from the traditional curved shape to a peaked version (recommended for snowy areas)
- Covering of extremely long-lasting storage sheeting 44/57-month warranty, available in different colours
- Optional covering of 650 gr/sq m PVC tarpaulin available in different colours
- Film fixed by means of aluminium profiles (wide range)
- Manual side fixing
- Film or polycarbonate headends with large hinged door
- Headends without doors and/or with roll-up opening
- The installation on the ground can be carried out by means of a base plate on slab or concrete footing, or, alternatively, with concrete foundation.

Note: Standard characteristics such as shelter length and height can be modified in order to meet the requirements of our customers.



## Base fixing with concrete

• Ø 70-82 outer tubes 

■

 Inner tubes of gavanized iron



Base plate





Standard width	Tube Ø	Tie-beam H	Ridge <b>H</b>
6.40 m	60 mm	2.40 - 4.10 m	3.70 - 5.65 m
8.00 m	60 mm	2.40 - 4.10 m	4.25 - 6.10 m
9.00 m	60 mm	2.40 - 4.10 m	4.30 - 6.60 m
10.00 m	60/76 mm	2.40 - 4.10 m	4.50 - 6.60 m
11.00 m	60/76 mm	2.40 - 4.10 m	4.80 - 6.90 m
12.00 m	60/76 mm	5.00 m	5.60 - 7.20 m